



## Key benefits

- Modern and elegant design without canopy
- Maximum product visibility with 7 loading levels
- Optimized merchandizing effectiveness

## Technology and Performance

- Reliable and robust construction
- No maintenance condenser
- Best in class energy performance 1,75 kWh/24h
- Easy serviceability with quick electrical connectors and easy access components
- Natural refrigerant R290
- Silent operation dBA <57
- Optimized airflow circulation with dual evaporator and condenser motors

## Standard configuration

- Top sticker on door
- Side stickers
- Vertical side LED
- Easy grip handle
- Electronic thermostat
- Metallic outer cabin, inner cabin and door
- 6 adjustable shelves
- Self-closing door
- 4 rollers / 2 adjustable feet

## Options

- Light switch
- Additional LED lighting
- Electronic controller
- PRCD protection
- RCCB protection
- Left/right door opening
- High density shelves
- Pad lock provision
- Door blocker



Best-in-class energy saving



Low noise

## Technical data

Dimensions	
External (W/D/H) mm	<b>595 x 639* x 2012</b>
Internal (W/D/H) mm	<b>521 x 491 x 1818</b>
Net weight (kg)	<b>100</b>
Footprint area (m <sup>2</sup> )	<b>0.38</b>

Shelves	
Number of shelves	<b>7</b>
Facings per shelf	<b>7</b>
Total facings (500ml PET)	<b>49</b>
Shelf size (W/D) mm	<b>508 x 423</b>

Capacity**	
500 ml PET	<b>259 cert.</b>
330 ml cans	<b>518 max.</b>
Gross volume (Lt)	<b>472</b>

Transportation	
per 40' container (units)	<b>57</b>
per 13.6m truck (units)	<b>76</b> (wide truck)
	<b>66</b> (standard truck)

\* 671 mm (including handle)